

Claims

- [1] A drying rack in a dryer comprising:
a rack detachably mounted to an inside of a drying drum for placing a drying object thereon; and
at least one drying stick for supporting the drying object spaced a predetermined distance from the rack.
- [2] The drying rack as claimed in claim 1, wherein the rack includes;
a seat having a plurality of pass through holes for pass through of drying air; and
a securing portion for supporting the seat spaced from a predetermined distance from an inside circumferential surface of the drying drum.
- [3] The drying rack as claimed in claim 1, wherein the drying stick is detachable from the rack.
- [4] The drying rack as claimed in claim 1, wherein the drying stick is formed to be extended upward from the rack.
- [5] The drying rack as claimed in claim 1, further comprising a seating plate at an end of the drying stick for seating the drying object thereon.
- [6] The drying rack as claimed in claim 5, further comprising a branch stick having one end fixedly secured to a side of the drying stick, and the other end supporting the seating plate.
- [7] The drying rack as claimed in claim 6, wherein the branch stick is formed as one body with the drying stick.
- [8] The drying rack as claimed in claim 6, wherein the end of the drying stick and the end of the branch stick are at the same height.
- [9] The drying rack as claimed in claim 1, wherein the drying stick has an upper end bent in a "U" shape.
- [10] The drying rack as claimed in claim 9, wherein the bent portion of the drying stick has a flat upper surface.
- [11] A drying rack in a dryer comprising:
a seat having a plurality of pass through holes for pass through of drying air;
a securing portion for supporting the seat spaced from a predetermined distance from an inside circumferential surface of the drying drum; and
a drying stick at the seat for drying the drying object in a space spaced a distance from the seat.
- [12] The drying rack as claimed in claim 11, wherein the drying stick is detachably

mounted projected upward from the seat.

- [13] The drying rack as claimed in claim 11, further comprising a branch stick at one side of the drying stick, the branch stick being branched in a direction different from the drying stick.
- [14] The drying rack as claimed in claim 13, wherein both the drying stick and the branch stick have ends at the same height.
- [15] The drying rack as claimed in claim 11, further comprising a seating plate at the end of the drying stick for seating the drying object.
- [16] The drying rack as claimed in claim 11, wherein the drying stick has an upper end bent in a "U" shape.
- [17] The drying rack as claimed in claim 16, wherein the bent portion of the drying stick has a flat upper surface.